

8165W 1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Reliable performance.



KEY FEATURES

- STANDARD Lifting Power
- WI-FI Built In

MyQ® Technology makes this opener compatible with multiple home automation platforms.

Visit LiftMaster.com/WorksWithMyQ for a full list of MyQ partners.*

RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY 4-YEAR MOTOR, 1-YEAR PARTS.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MyQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

SECURE

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®
Includes lockout controls and accessory programmability.

882LMW

3-BUTTON REMOTE CONTROL
Operates up to 3 openers or MyQ Light Accessories.

893LM

POWERFUL ADD-ONS:

MyQ HOME BRIDGE
Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.**

819LMB

MINI UNIVERSAL REMOTE CONTROL
Compact and portable to provide quick, easy garage access.

374UT

REMOTE LIGHT CONTROL
Plug in any lamp to this device to control it with a smartphone or garage remote.

825LM

REMOTE LIGHT SWITCH
Replaces an existing wall switch to control home lighting with a smartphone or garage remote.

823LM

GARAGE DOOR AND GATE MONITOR
Monitors and closes up to 4 garage doors from any room in the house.

829LM

*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee. Smartphone not included.
**Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV® with tvOS™ 10.0 or later or an iPad® with iOS 10.0 or later set up as a home hub.

PRODUCT GUIDE 8165W
1/2 HP AC CHAIN DRIVE WI-FI
GARAGE DOOR OPENER



For more information, please visit www.devancocanada.com or call toll free at 855-931-3334

8165W

MASTERFUL ENGINEERING.

1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

MOTOR



- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 6A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

MECHANICS



- Steel Chassis, T-Rail and Trolley
- Full Chain Drive Mechanism (16:1 Gear Reduction and Adjustable Door Arm)
- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- AC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)

5.75"



15"

10"

DIMENSIONS

| | | | |
|------------------|------|------|-------|
| Rail Options | 7' | 8' | 10' |
| Installed Length | 124" | 136" | 160" |
| Max. Opening | 7'6" | 8'6" | 10'6" |

Headroom Clearance Required: 2"

7"

Per second for door to move upward

SPEED

7"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

3-Button Remote Control (893LM)

Operating Range: ~200'

Operating Temperature: -30°F to 150°F
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY+ 2.0

ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 1 100-Watt Lightbulb
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)



HEAD



RAIL (7')

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882LMW)
- 3-Button Remote Control (893LM)
- Garage Door Opener Head (8165W)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.



- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 MyQ Devices

†WARNING: to reduce the risk of injury to persons— ONLY enable Timer-to-Close and MyQ remote operation features when opener is installed on a sectional door.

ALARM.COM is a registered service mark of Alarm.com.
 Apple is a trademark of Apple Inc., registered in the U.S. and other countries. HomeKit is a trademark of Apple Inc.
 Clare Controls is a registered trademark of Clare Controls, Inc.
 Google, Google Home, Google Assistant and other related marks and logos are trademarks of Google Inc.
 Nest is a trademark of Nest Labs, Inc.
 XFINITY Home and the XFINITY Home design logo are trademarks or service marks of Comcast Corporation.
 UL and the UL logo are trademarks of UL LLC © 2018 All Rights Reserved.
 Wi-Fi® is a registered trademark of Wi-Fi Alliance
 HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation
 LMGDENPG8165W 3/18



For more information, please visit www.devancocanada.com or call toll free at 855-931-3334